
TORNADO DIRECT




Direct unvented stainless-steel hot water storage cylinder with built-in thermal expansion.

Tempest Direct hot water storage cylinders are particularly suited to smaller properties where electricity is the only available heat source. Manufactured from Duplex stainless-steel, the cylinders are supplied with two, factory-fitted 3kW immersion heaters which provide the option of heating water on different schedules, tariffs and configurations.

FEATURES & BENEFITS

- ✓ Duplex stainless steel provides superior corrosion resistance
- √ 316L grade stainless-steel 22mm compression fittings and coils
- ✓ Supplies mains pressure hot water and high flow rates
- ✓ Fast reheat
- ✓ Factory-fitted temperature and pressure relief value set at 7 bar / 90°C
- ✓ Built-in thermal expansion no external expansion vessel required
- ✓ Full unvented kit supplied
- ✓ Highly efficient
- ✓ Fully insulated to minimise any heat loss
- ✓ 2 x factory-fitted 3kW immersion heaters
- ✓ Available in 90-300 litre capacities
- ✓ Lifetime manufacturing warranty on inner container (2 years on components)
- ✓ Renewable and bespoke options available




















TECHNICAL DATA





Capacity (L)	125	150	170	200	250	300
Height (mm)	1025	1260	1325	1550	1800	2050
Diameter (mm)	580	580	580	580	580	580
A (mm)	178	178	178	178	178	178
B (mm)	200	200	200	200	200	200
C (mm)	495	495	495	495	495	495
D (mm)	665	900	965	1020	1250	1400
E (mm)	800	950	1065	1150	1350	1500

Capacity (L)	125	150	170	200	250	300
Reheat from cold (minutes)	72	86	98	108	144	202
Reheat from 75% draw-off (minutes)	37	45	51	63	75	136
ERP Rating*	С	С	С	С	С	С
Immersion Rating (kW)	2 x 3	2 x 3	2 x 3	2 × 3	2 x 3	2 x 3
Standing Heat Loss (kWh/24hrs)	1.17	1.24	1.27	1.53	1.68	1.87

^{*}Based on thermostat set a 60°C